CAD-CUT[®] BASIC FILM

SMOOTH AND MATTE PU MATERIAL THAT PROVIDES OPTIMAL OPACITY

There is no back-adhesive carrier which makes it perfect for large designs, numbers and letters as the film is so easy to weed.

Low cost - very easy to process (no need for capitalizing).





AVAILABLE IN

50 cm x 25 m roll

RECOMMENDED FABRICS * Test before application!

- 100% Cotton
- 100% Polyester*
- Polyester-Cotton blends

CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. To ensure optimum processing of the material, a minimum line thickness of 1.5 mm is required.

APPLICATION INSTRUCTIONS

Temperature:	160° C
Time:	10 sec.
Pressure:	Medium (#4-6 with Hotronix [®])
Carrier:	Cold peel

MULTI-COLOR DESIGNS

Print the background for 3-5 seconds, peel off the carrier cold. Repeat the process for each additional color. Print the last color for 18 - 20 seconds. Remove the carrier cold.

ACCESSORIES RECOMMENDED

- \cdot Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers

Washable up to 60° C. Please do not use fabric softener or bleach. Wash inside out and iron.

CARE INSTRUCTIONS

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

DETAILS







80

MEDIUI