
## **CAD-CUT® PREMIUM PLUS**



# THIN AND ELASTIC FLEX FILM - SOFT FEEL & SILK-MATT FINISH.

Polyurethane (PU) flex film, which is characterized by high opacity and a matt surface finish. Soft to the touch, therefore perfect for large motifs. Easily back-adhesive carrier. Easy to cut and weed. Suitable for multi-colored prints.



#### **AVAILABLE IN**

- 30 cm x 25 m roll\* 100 cm x 25 m roll
- 50 cm x 25 m roll
- \* Minimum order quantity 3 rolls plus 15 € cutting costs

#### RECOMMENDED FABRICS \* Test before application!

- 100% Cotton Polyester-Cotton blends
- $\cdot$  100% Polyester\* /Polyester Mesh  $\cdot$  Lycra $^{\circ}$  / Spandex mixed blends
- · Nylon\*\* · Satin

#### **CUTTING NOTES**

Always test the cutting settings before production. The settings depend on the age of the blade used. To ensure optimum processing of the material, please only plot logos with a minimum line thickness of 2 mm.

#### **APPLICATION INSTRUCTIONS**

Temperature:  $130^{\circ}$  C /  $150^{\circ}$  C Time: 10 sec. / 5 sec.

Pressure: Medium (#4-6 with Hotronix®)

Carrier: Hot peel / \*\*Nylon carrier: cold peel

#### **MULTI-COLOR DESIGNS**

Print the background for 3-5 seconds, peel off the carrier cold. Repeat the process for each additional color. Print the last color for 18-20 seconds. Peel off the carrier hot.

### **ACCESSORIES RECOMMENDED**

- · Grip Cover Sheet
- · Cover Sheet Non-Sticky
- · EZ Weeder®, LED Weeder, LED Pin or Tweezers

#### **CARE INSTRUCTIONS**

Washable up to  $60^{\circ}$  C. Please do not use fabric softener or bleach. Can be ironed directly.

#### **STORAGE**

Store in a cool, dry environment. Avoid direct heat or sunlight.

#### **DETAILS**



























